

**ALSEAL MARKETING SDN. BHD.****Safety Data Sheet****AS-4030
MS Flooring Adhesive**

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

1. Identification of the substance/preparation and of the company/undertaking**Product name** : AS-4030 MS Flooring Adhesive**Product use** : MS adhesive**Company** : Alseal Marketing Sdn. Bhd.
Lot 2291, Jalan Kampung Baru,
Kg. Baru Sungai Buloh,
47000 Selangor, Malaysia.**Telephone** : +603 - 6157 9698**Fax** : +603 - 6157 8002**Email** : info@alsealmarketing.com**Website** : www.alsealmarketing.com**2. Hazard(s) identification****Substance/Mixture** : Mixture**Hazard classification** : Not classified as hazardous**Pictogram** : Not classified as hazardous**Signal word** : Not classified as hazardous**Hazard statement(s)** : Not classified as hazardous**Precautionary statement(s)** : Not classified as hazardous**Other hazards which do not result in classification but contribute to overall hazards:** None known**3. Composition/Information on ingredients**

Chemical name	CAS No.	EINECS No.	%
Limestone	1317-65-3	215-279-6	50 - 70
Diisononylphthalate	28553-12-0	249-079-5	10 - 30
3-(2-aminoethylamino)propyltrimethoxysilane	1760-24-3	217-164-6	0.1 – 1.0
Dibutyltin bis(acetylacetonate)	22673-19-4	245-152-0	0.1 – 1.0

4. First-aid measures**In case of inhalation:**

Remove to fresh air, keep warm and at rest. Contact physician if symptom persists.

In case of skin contact:

Remove contaminated clothing. Rinse with copious amount of water and soap. Get medical advice if skin irritation or a rash occurs. Wash clothing before reuse.

In case of eye contact:



ALSEAL MARKETING SDN. BHD.
Safety Data Sheet
AS-4030 MS Flooring Adhesive

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

Contact lenses should be removed. Rinse with copious amount of water immediately. Seek medical advice if eye irritation develops and persists.

In case of ingestion:

DO NOT induce vomiting. Rinse mouth thoroughly with water. Get medical attention if a symptom persists.

Personal protection equipment for first-aiders:

Pay attention to any potential hazards and use recommended personal protection equipment if potential for exposure exists.

Most important symptoms and effects, acute and delayed:

None known.

5. Fire-fighting measures

Suitable extinguishing media:

Water, alcohol-resistant foam, carbon dioxide, dry chemical.

Unsuitable extinguishing media:

None known.

Specific firefighting procedures:

Remove undamaged containers from fire area if it is safe to do so. Use extinguishing media that is suitable to local circumstances and surrounding environment.

Special person protection equipment for firefighters:

NIOSH-approved self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Specific hazards arising from firefighting:

Exposure to combustion products may be a hazard to health.

Thermal decomposition products:

Carbon dioxide, carbon monoxide, nitrogen oxides, and other irritant gases.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedure:

Use recommended personal protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Measure for cleaning/collecting:

Wipe or soak with inert liquid binding material (sand, sawdust, etc.). Scrape away cured material. Dispose the spilt material according to local or national regulations. Section 13 of this safety data sheet provides information regarding certain local or national requirements.


Additional information:

Prevent spillage from entering drainage/sewer systems. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

7. Handling and storage

Handling:

Ensure good ventilation during use. Avoid contact with skin and eyes. Do not eat, drink, or smoke when using the product.

	ALSEAL MARKETING SDN. BHD.
	Safety Data Sheet
	AS-4030 MS Flooring Adhesive

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

Storage:

Ensure containers and cartridges are tightly closed. Store in a dry, well-ventilated area, and protected from direct sunlight with temperature not exceeding 30 °C. Keep away from incompatibles. Refer to section 10 for incompatible materials.

8. Exposure controls/personal protection

Components	CAS No.	Form of exposure (Value type)	Control Parameter	Basis
Limestone	1317-62-3	8 hours TWA (Particulate matter containing no asbestos and <1% crystalline silica)	10 mg/m ³	Malaysia OSHA
Limestone (total dust)	1317-62-3	8 hours TWA	10 mg/m ³	US OSHA
Limestone (respirable fraction)	1317-62-3	8 hours TWA	5 mg/m ³	US OSHA
Limestone (inhalable dust)	1317-62-3	8 hours TWA	10 mg/m ³	UK WEL
Limestone (respirable dust)	1317-62-3	8 hours TWA	4 mg/m ³	UK WEL
Limestone	1317-62-3	8 hours TWA (Particulate matter containing no asbestos and <1% crystalline silica)	10 mg/m ³	Safe Work Australia
Diisononylphthalate	28553-12-0	8 hours TWA	5 mg/m ³	UK WEL

Engineering controls:

Product curing may form hazardous compounds. Ensure adequate ventilation and minimise workplace exposure concentrations.

Industrial hygiene:

Remove immediately all contaminated clothing. Do not inhale vapour. Wash hands and contaminated areas with water and soap before leaving the work site. Change clothing before leaving workplace and wash before reuse. Do not eat, drink, or smoke while using product.

Hand protection:

Suitable impervious protective gloves (latex, nitrile, etc.). Breakthrough time is not tested for this product. Change gloves often if possible.

Respiratory protection:

A NIOSH-approved respirator with filter for organic vapours is recommended where local ventilation is not adequate.

Eye/Face protection:

Protective goggles/safety glasses.

9. Physical and chemical properties

**ALSEAL MARKETING SDN. BHD.****Safety Data Sheet****AS-4030
MS Flooring Adhesive**

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

Appearance	: Thixotropic paste
Odour	: Characteristic odour
Odour threshold	: Not determined
pH	: Not applicable
Freezing/Melting point	: Not determined
Boiling point range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability	: Not classified as flammable
Explosive properties	: Not classified as explosive
Oxidising properties	: Not classified as oxidising
Vapour pressure	: Not applicable
Vapour density	: Not applicable
Relative density	: Approximately 1.56
Solubility in water	: Not determined
N-octanol/water partition coefficient	: Not determined
Decomposition temperature	: Not determined
Viscosity	: Not applicable
VOC content (USEPA Method 24)	: 9.49 g/L

10. Stability and reactivity**Reactivity:**

No reactive hazards known.

Stability:

Stable under recommended handling and storage conditions.

Conditions to avoid:

Exposure to water/water vapour and humid air.

Hazardous reactions:

Hazardous polymerisation will not occur.

Hazardous decomposition products:

None known.

Incompatible materials:

Water, alcohol, and amines.


11. Toxicology information

No specific oral, inhalation or dermal toxicology data is known for this product. Any toxicological data included in this section is based on the data associated with the components.

Acute oral toxicity, LD₅₀ (rat):

Not classified based on available information and/or concentration of components.

Limestone	>2,000 mg/kg
Diisononylphthalate	>10,000 mg/kg

	ALSEAL MARKETING SDN. BHD.
	Safety Data Sheet
	AS-4030 MS Flooring Adhesive

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

3-(2-aminoethylamino)propylmethoxysilane	2,295 mg/kg
Dibutyltin bis(acetylacetonate)	1,864 mg/kg

Acute dermal toxicity, LD₅₀ (rabbit):

Not classified based on available information and/or concentration of components.

Diisononylphthalate	>3,160 mg/kg
3-(2-aminoethylamino)propylmethoxysilane	2,000 mg/kg
Dibutyltin bis(acetylacetonate)	>2,000 mg/kg

Acute inhalation toxicity, LC₅₀ (4 hours, rat):

Not classified based on available information and/or concentration of components.

Diisononylphthalate	>4.4 mg/L (aerosol)
3-(2-aminoethylamino)propyltrimethoxysilane	>1.49 mg/L (mist)

Serious eye damage/eye irritation:

Not classified based on available information and/or concentration of components.

Limestone	Not eye irritant.
Diisononylphthalate	Not eye irritant.
3-(2-aminoethylamino)propylmethoxysilane	Irreversible effects on the eye.
Dibutyltin bis(acetylacetonate)	Causes eye irritation.

Skin corrosion/skin irritation:


Not classified based on available information and/or concentration of components.

Limestone	Not skin irritant.
Diisononylphthalate	Very mild skin irritation.
3-(2-aminoethylamino)propylmethoxysilane	Not skin irritant.
Dibutyltin bis(acetylacetonate)	Causes skin irritation.

Respiratory/Skin sensitisation:

Not classified based on available information and/or concentration of components.

Limestone	Not sensitising on skin.
-----------	--------------------------

	ALSEAL MARKETING SDN. BHD.
	Safety Data Sheet
	AS-4030 MS Flooring Adhesive

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

Diisononylphthalate	Not sensitising to respiratory and skin.
3-(2-aminoethylamino)propylmethoxysilane	Probability or evidence of skin sensitisation in humans.
Dibutyltin bis(acetylacetonate)	Sensitising on skin.

Germ cell mutagenicity:

Not classified based on available information and/or concentration of components.

Limestone	Negative genotoxicity <i>in vitro</i> .
Diisononylphthalate	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Dibutyltin bis(acetylacetonate)	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .

Carcinogenicity:

Not classified based on available information and/or concentration of components.

Diisononylphthalate	Negative carcinogenicity. NOAEL: 88.3 mg/kg bw/day
Dibutyltin bis(acetylacetonate)	No statistically significant increase in tumour incidences. NOAEL: 152 ppm

Reproductive toxicity:

Not classified based on available information and/or concentration of components.

Limestone	No effect on fertility and foetal development.
Diisononylphthalate	No effect on fertility and foetal development.
3-(2-aminoethylamino)propylmethoxysilane	No effect on fertility and foetal development.
Dibutyltin bis(acetylacetonate)	No data on fertility. No effect on foetal development.

Specific target organ toxicity – single exposure:


Not classified based on available information and/or concentration of components.

3-(2-aminoethylamino)propylmethoxysilane	Exposure by ingestion. No significant health effect at concentration of 100 mg/kg bw or less.
--	--

Specific target organ toxicity – repeated exposure:

Not classified based on available information and/or concentration of components.

Limestone	Exposure for 6 weeks by ingestion on rats. NOAEL: 1,000 mg/kg
Diisononylphthalate	Exposure for 104 weeks by ingestion on rats. NOAEL: 88.3 mg/kg bw/day
	Exposure by inhalation on rats. NOAEC: 500 mg/m ³

	ALSEAL MARKETING SDN. BHD.
	Safety Data Sheet
	AS-4030 MS Flooring Adhesive

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

	Exposure for 6 weeks by dermal on rabbits. NOAEL: 500 mg/kg bw/day
3-(2-aminoethylamino)propylmethoxysilane	Exposure by ingestion for 28 days on rats. NOAEL: 500 mg/kg bw/day
	Exposure by dermal for 11 days on rats. NOAEL: 1,545 mg/kg bw/day
Dibutyltin bis(acetylacetonate)	Exposure by ingestion for 2 weeks on rats. NOAEL: <50 ppm LOAEL: 50 ppm

Aspiration toxicity:

Not classified based on available information and/or concentration of components.

Likely route of administration:

Inhalation, skin contact, and ingestion.

12. Ecological information

Individual components of this mixture have been independently tested by the raw material suppliers and any known results have been presented below. The results for the individual components may not be representative of the ecological toxicity of this finished product. This finished product has not been tested to determine individual toxicological/ecological limits.

Ecology toxicity:


No adverse effect on aquatic organisms is predicted based on available information and/or concentration of components.

Limestone Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC ₅₀ : >100 mg/L Exposure for 48 hours, EC ₅₀ : >100 mg/L Exposure for 72 hours, EC ₅₀ : >14 mg/L
Diisononylphthalate Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC ₅₀ : >102 mg/L Exposure for 48 hours, EC ₅₀ : >74 mg/L Exposure for 72 hours, EC ₅₀ : >88 mg/L
3-(2-aminoethylamino)propylmethoxysilane Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC ₅₀ : 597 mg/L Exposure for 48 hours, EC ₅₀ : 81 mg/L Exposure for 72 hours, EC ₅₀ : 8.8 mg/L
Dibutyltin bis(acetylacetonate) Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC ₅₀ : >2 mg/L Exposure for 48 hours, EC ₅₀ : 168.7 mg/L Exposure for 7 days, EC ₅₀ : 210 mg/L

Persistence and degradability:

Not likely to be persistent based on available information and/or concentration of components.

Diisononylphthalate	Readily biodegradable. Exposure for 28 days, 81% biodegradation.
3-(2-aminoethylamino)propylmethoxysilane	Not readily biodegradable. 39% biodegradation. 0.025 hours half-life degradation.

	ALSEAL MARKETING SDN. BHD.
	Safety Data Sheet
	AS-4030 MS Flooring Adhesive

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

Bioaccumulative potential:

No bioaccumulation potential based on available information and/or concentration of components.

Diisononylphthalate	BCF: <3
3-(2-aminoethylamino)propylmethoxysilane	Log K _{ow} : -0.3

Mobility in soil:

No data available.

13. Disposal information

Waste treatment/disposal methods - unused products

Waste disposal must be in compliance with environmental protection requirements and local regulations.

Waste treatment/disposal methods - contaminated packaging

Dispose of as unused product. Empty container should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Road transport (UNRTDG) : Not regulated as dangerous goods.
UN number : Not applicable
Proper shipping name : Not applicable
Technical name : Not applicable
Hazard class : Not applicable
Classification code : Not applicable
Packing group : Not applicable

Marine transport (IMDG) : Not regulated as dangerous goods.
UN number : Not applicable
Proper shipping name : Not applicable
Technical name : Not applicable
Hazard class : Not applicable
EmS : Not applicable
Packing group : Not applicable
Marine pollutant : Not applicable

Air transport (IATA) : Not regulated as dangerous goods.
UN number : Not applicable
Proper shipping name : Not applicable
Technical name : Not applicable
Hazard class : Not applicable
Packing group : Not applicable

15. Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical in question:

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2010 (Malaysia)

**ALSEAL MARKETING SDN. BHD.****Safety Data Sheet****AS-4030
MS Flooring Adhesive**

Issued date: 02/11/16

Revision date: 07/04/18

Revision No.: 4

Occupational Safety and Health (Classification, Labelling, and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 (Malaysia)

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (European Union)

Occupational Safety and Health Administration (OSHA) (2006) Air Contaminants. 29 CFR 1910.1000 (United States of America)

Work Health and Safety Act 2011 (Australia)

EH40/2005 Workplace exposure limits (United Kingdom)

Chemical inventory status:

Australia AICS : All ingredients listed or exempt.
Canada DSL : All ingredients listed or exempt.
Japan ENCS : All ingredients listed or exempt.
Korea KECI : All ingredients listed or exempt.
Taiwan ECSN : All ingredients listed or exempt.

16. Other information**Definitions:**

TWA : Time-weighted average.
STEL : Short-term exposure level.
OSHA : Occupational Safe and Health Act
WEL : Workplace exposure limits
LD₅₀ : The minimum dose required for lethal effects in 50% of a given population of test specimens.
ppm : part per million
bw : body weight
BCF : Bioconcentration factor
NOAEL : No-observed-adverse-effect-level
LOAEL : Lowest-observed-adverse-effect level
NIOSH : National Institute for Occupational Safety and Health.
UNRTDG : United Nations Recommendations on the Transport of Dangerous Goods
IMDG : International Maritime Dangerous Goods
IATA : International Air Transport Association
AICS : Australian Inventory of Chemical Substances
DSL : Domestic Substance List
ENCS : Existing and New Chemical Substances.
KECI : Korea Existing Chemicals Inventory.
ECSN : Existing Chemical Substance Nomination.

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The details contained herein are based on our present state of knowledge and experience in characterising our product with regard to any possible safety requirement at the date of its publication. We do, however, pass them on without any warranty or property assurances.